NOVAFLEX NY SERIES INK

1.PRODUCT DESCRIPTION

Gold and silver ink series designed for flexographic printing, suitable for printing on all packaging materials used in water-based ink series.

2. PRODUCT FEATURES

1	2	3	4	5	6	7	8	9	10	
MIN.									MA	Х.

BRIGHTNESS	9
FRICTION RESISTANCE	8
WATER RESISTANCE	8
DRYING SPEED	10
COLOR STRENGTH	9

3.APPLICATIONS

Suitable for surface printing on all paper, cardboard, napkins, PE, PP film and other packaging products. ***

Stir before use.

The printing viscosity is 18-22 sec (Din cup N ° 4). The product should be diluted with water. Never mix solvent. The corona range of the film surface to be applied must be 38-42 dyne/cm

SUITABLE INK ADDITIVES

- Novaflex Antifoam
- Novaflex Retardant
- Novaflex Accelerator
- Novaflex Waxy Additive

TEKNOVA MATBAACILIK KİMYA SANAYİ VE TİCARET A.Ş.AKÇABURGAZ MAHALLESİ 3101.SOKAK 34522 ESENYURT/İSTANBUL/ TÜRKİYETEL: +90 212 485 37 00FAX: +90 212 485 20 80E-Mail: export@teknova.com.trWeb Site: http://www.teknova.com.tr

For further information: kalite@teknova.com.tr

NOVAFLEX NY SERIES INK

4.TECHNICIAL SPECIFICATIONS

COLOUR	Spesific				
RESOLUTION	Solubility in Water				
рН	7,5-8,5				
VISCOSITY	20-25 sec. (Din4/20-25°C)				
SMELL	Characteristic				

5.STORAGE

Ideally, the appropriate storage temperature of the product should +5°C/+30°C Product shold be avoid from freezing.

The shelf life of the product is 6 months in its original packaging under ideal storage conditions. It should be consumed in a short time after opening.

6.SAFETY

When using this product, please follow the advice and information given in the safety data sheet. Use adequate protective equipment to work with chemicals and follow hygiene measures at the workplace. Dispose according to local / regional / national regulations regarding the disposal of hazardous waste.

PACKAGING: 20 KG, 200 KG, 1000 KG

NOTE:

The purpose of this technical document is to provide users with general information about the product. According to the experiments carried in our laboratory and in addition to our experience in the field, the data we have collected may not conform with the required application due to the several external factors. Therefore, these data cannot guarantee the suitability of the product for a particular purpose or the specific properties. The correct application for each product should be carefully checked for suitability. Therefore, this recommendation cannot be used as a basis for claims in law. It is the responsibility of the purchaser of our product to ensure compliance with all property rights, existing laws and regulations.

TEKNOVA MATBAACILIK KİMYA SANAYİ VE TİCARET A.Ş.AKÇABURGAZ MAHALLESİ 3101.SOKAK 34522 ESENYURT/İSTANBUL/ TÜRKİYETEL: +90 212 485 37 00FAX: +90 212 485 20 80E-Mail: export@teknova.com.trWeb Site: http://www.teknova.com.tr

For further information: kalite@teknova.com.tr